

The Art and Science of Light

SPECIFICATIONS:

models: CRm e50 and e100
 primary power: 120V, 277V
 compliance: UL Listed
 control: Dimming compatible
 fixture housing: Clear anodized aluminum
 dimensions: 4' to 7'6" and custom lengths
 lamp color(s): see color chart on Details sheet
 update: April 6, 2012

FEATURES:

cCRVSm mini offers standard and custom curved lamps with seamless, end-to-end illumination, free from socket shadow. Using state of the art, silent, energy efficient electronic power supplies, cCRVSm mini are more compact than traditional cold cathode systems. cCRVSm mini fixtures ship pre-wired and assembled for installation in minutes resulting in significant labor savings. cCRVSm mini features ACL's new "Snap and Slide" extrusions for easy access to lamps and ballasts. cSTRPmini can be daisy-chained using our pre-wired "Easy Connect" system. Single lamp configurations are available in a wide range of colors. Combining cCRVSm mini with cSTRPmini allows for enhanced flexibility to fit any design solution.



cCRVSm mini CUT SHEET

Project Name _____

Linear Feet _____

Date _____

SPECIFICATION CODE:

Product	Model	Environment	Color(s)	Primary	Dimming	Mount
cCRVSm mini Cold Cathode	e50 (1) e100 (1)	DR - Dry	See Color Chart (2)	120V 277V	2 - 2 Wire (3) 3 - 3 Wire (3)	S - Surface

(1) e50 - Energy Saver, e100 - Standard Output.

(2) For multiple colors place a comma after each selection. (3) Reverse phase low-voltage electronic dimmers are recommended for optimal performance.

Specifications subject to change without notice.



Architectural Cathode Lighting, Incorporated

cathodelighting.com

5301 Pacific Boulevard
 Huntington Park California 90255 USA
 Telephone 323.581.8800
 Fax 323.581.7971
info@cathodelighting.com