

The Art and Science of Light

SPECIFICATIONS:

model: SL01/SL02/SL03
primary power: 120V, 277V
Compliance: UL Listed
control: Dimming Compatible
finish: Clear Anodized Aluminum
dimensions: 4'6", 5'6", 6'0", 6'6"
lamp color(s): See color chart on Details Sheet
update: August 23, 2012

FEATURES:

New and improved Streamlite 2.0 offers a creative way to illuminate an interior space. ACL's new threaded eCVR with no visible fasteners make this luminaire even more sleek and minimalistic giving the impression of light floating in space. Streamlite 2.0 Cold Cathode lamps have end to end illumination, and are available in several standard lengths and colors. The armature mounted lamps include various methods for integrating the power supply. Streamlite 2.0 can be suspended from ceilings, mounted to walls, installed in coves, freestanding and more. The luminaire offers unlimited possibilities that are both classic and timeless.

STREAMLITE CUT SHEET



©2012 Architectural Cathode Lighting, Inc.

Project Name _____ Qty _____ Date _____

SPECIFICATION CODE:

Product	Model	Power Supply	Environment	Color (1)	Primary	Dimming (2)	Lamp Dimension
Streamlite Cold Cathode	SL01 - Armature Mount SL02 - Ceiling Mount SL03 - Remote Mount	e50 - Energy Saver e100 - Standard Output e200 - High Output	DR - Dry	See Color Chart	120V 277V	2- 2 Wire 3- 3 Wire	4' to 6'6"

(1) For multiple colors place a comma after each selection. (2) Reverse phase low-voltage electronic dimmers are recommended for optimal performance. 4' Cable and power drop standard. Can be field adjusted. For custom length contact ACL.

Specifications subject to change without notice. 073112

ACL INC.

Architectural Cathode Lighting, Incorporated
cathodelighting.com

5301 Pacific Boulevard
 Huntington Park, California 90255 USA
 Telephone 323.581.8800
 Fax 323.581.7971
 info@cathodelighting.com