

STREAMLITE DETAILS



- A creative way to illuminate any interior space.
- Armature mounted lamps with end-to-end illumination.
- Multiple power supply mounting options.
- Reliable, proven technology with 50,000 hour lamp life.
- Dimming, silent, energy efficient power supplies.
- Available in standard lengths from 4' to 6'6".
- Clear anodized finish.
- 11 hues of white and 30+ colors with high CRI.
- Up to 780 lumens per foot and 78 lumens per watts.

Electrical + Lumen Data

e50 Electrical Specifications

Volts	Amps	Watts *	Lumens *	Lumens/Watts
120	.35	4.5	307	68
277	.14	4.5	307	68

e100 Electrical Specifications

Volts	Amps	Watts *	Lumens *	Lumens/Watts
120	.46	6.6	521	79
277	.20	6.6	521	79

e200 Electrical Specifications

Volts	Amps	Watts *	Lumens *	Lumens/Watts
120	.78	12.6	780	78
277	.35	12.6	780	78

* Per Linear Foot, based on 7'6" lamp at 3500k



Contact ACL for additional color options.

ACL INC.

Architectural Cathode Lighting, Incorporated
cathodelighting.com

5301 Pacific Boulevard
 Huntington Park, California 90255 USA
 Telephone 323.581.8800
 Fax 323.581.7971
 info@cathodelighting.com

Project Name		Qty		Date			
SPECIFICATION CODE:							
SL	-	-	DR	-	-	-	-
Product	Model	Power Supply	Environment	Color (1)	Primary	Dimming (2)	Lamp Dimension
Streamlite Cold Cathode	S01 - Armature Mount S02 - Ceiling Mount S03 - Remote Mount	e50 - Energy Saver e100 - Standard Output e200 - High Output	DR - Dry	See Color Chart	120V 277V	2 - 2 Wire 3 - 3 Wire	4' to 6'6"

(1) For multiple colors place a comma after each selection.
 (2) Reverse phase low-voltage electronic dimmers are recommended for optimal performance.
 Specifications subject to change without notice. 073112