The Art and Science of Light

SPECIFICATIONS:

models: CSm e50 and e100 primary power: 120V, 277V compliance: UL Listed control: Dimming compatible fixture housing: Clear anodized aluminum dimensions: 2' to 7'6" and custom lengths lamp color(s): See color chart on Details sheet update: April 6, 2012

FEATURES:

cSTRPmini offers standard and custom straight lamps with seamless, end-to-end illumination, free from socket shadow. Using state of the art, silent, energy efficient electronic power supplies, cSTRPmini are extremely more compact than traditional cold cathode systems. cSTRPmini fixtures ship pre-wired and assembled for installation in minutes resulting in significant labor savings. cSTRPmini features ACL's new "Snap and Slide" extrusions for easy access to lamps and ballasts. cSTRPmini can be daisy-chained using our pre-wired "Easy Connect" system. Single lamp configurations are available in a wide range of colors. Combining cSTRPmini with cCRVSmini allows for enhanced flexibility to fit any design solution.





Project Name						Linear Feet	
SPECIFI	CATIONC	ODE:					
CSm		DR				<u>- S</u>	
Product	Model	Environment	Color(s)	Primary	Dimming	Mount	
cSTRPmini Cold Cathode	e50(1) e100(1)	DR - Dry	See Color Chart (2)	120V 277V	2 - 2 Wire (3) 3 - 3 Wire (3)	S - Surface	



. .

5301 Pacific Boulevard Huntington Park California 90255 USA Telephone 323.581.8800 Fax 323.581.7971 info@cathodelighting.com

(1) e50 - Energy Saver, e100 - Standard Output.

(2) For multiple colors place a comma after each selection. (3) Reverse phase low-voltage electronic dimmers are recommended for optimal performance. Specifications subject to change without notice.