

A Fusion of the Art and Science of Light

SPECIFICATIONS:

model: Cathode T100
primary power: 120V, 277V special order
compliance: UL Listed
control: color changing / dimming compatible
mounting: surface
environment: damp or dry
lamp color(s): See color chart on Detail sheets
date: August 21, 2008

FEATURES:

Cathode T100 is ACL's cold cathode transformer system that can be placed in coves with conduit feed for an easy and economical installation. Cathode T100 has a significant extended lamp life and has no socket shadows and requires no lamp overlap. Cold Cathode comes in a variety of colors, with economical dimming available with many commercial dimming systems. If your project calls for a brighter cathode lighting system, Cathode T100 has brighter lamp output than many other cathode systems. They are perfect for commercial applications.



© 2008 Architectural Cathode Lighting, Inc.

CATHODE T100
 CUT SHEET

SPECIFICATION CODE: Note: For a variation (custom) of this product contact ACL to request a variation number and information.

T100 (1)	-	S01	-	-	-	-	S
Product	Standard	Environment	Color (s)	Primary	Dim-able	Mount	
Standard Output 7 Lamp Transformer Cold Cathode System	S01	DR - Dry DP - Damp	See Chart on Detail sheets (2)	120V 277V-Special Order	DI - Dim ND - Non Dim	S - Surface	

(1) For our lower output system; T50, contact ACL. For a 1 lamp standard ballast system see B100. For a 2 lamp high output ballast system see B200.
 (2) For multiple selections place a comma after each selection.

ACL INC.
 Architectural Cathode Lighting, Incorporated
cathodelighting.com

5301 Pacific Boulevard
 Huntington Park California 90255 USA
 Telephone 323.581.8800
 Fax 323.581.7971
info@cathodelighting.com