



Imagine rows of vertical shafts of light that border a walkway, an entrance, or a progression of light sculptures winding through a plaza.

Litetower is 6.5" in diameter and is available in a variety of heights. The construction includes a translucent high impact acrylic DR outer tube, with an inner structural steel tube for secure mounting and housing all electrical components. Litetower is available with 1, 2 or 3 lamps. Lamps can be monochromatic or a combination of colors for a dramatic color-changing effect.

Litetower is UL listed for dry and wet locations.

Exciting materials such as brushed stainless steel cladding and stainless steel mesh can be wrapped around the acrylic tubing to create unique installations for every project.





SPECIFICATIONS:

primary power: 120V, 2 AMPS, 180 VA, 60 Hz per lamp

models: LT 001 / LT 002

(see technical sheet for additional configuration options)

compliance: UL Listed

control: color changing / dimming compatible
finish: combination of frosted acrylic DR / stainless steel
base cover / brushed stainless steel cladding / stainless

steel mesh (other finishes and materials upon request) dimensions: up to 12' max. height / diameter 6.5"/

base cover diameter 12"

lamp colors: available in 3000°K TC, 3500°K white, 2400°K incandescent, warm white, red, blue, green, orange, gold, and many other standard colors.



cathodelighting.com

5301 Pacific Boulevard

Huntington Park California 90255 USA Telephone 323.581.8800 Fax 323.581.7971

info@cathodelighting.com